

# Product Summary

Accessories for your pipeline needs.

PO Box 60399  
Lafayette, LA 70596-0399  
Toll Free: (800) 315-6099  
sales@apsonline.com  
www.apsonline.com  
ISO 9001:2015 Registered

## Flange Isolating Gasket Kits

Full, raised, or ring joint gaskets; in Buna-N faced phenolic, Durabla, NEMA Grade G-3, G-7, G-10 and G-11 with accompanying isolating double washers of phenolic, Mylar, polyethylene, Nomex, G-10 and one-piece bolt sleeves of Minlon. The Trojan and Quad Seal G-10 gaskets are also NSF-61 approved. Sizes available from 1/2" to 150" diameter.




## UBolt-Cote® and Atlas® Pipe Support Pads

Polyolefin or fusion applied polymer coated UBolts used for corrosion resistance and cathodic protection. Atlas® Pipe Supports provide zero water absorption, UV protection and minimal contact between pad and pipe, eliminating crevice corrosion.



## Kleerband® Flange Protector

Prevents corrosion from developing between flanges on piping systems. Clear-extruded polymer band with grease injection fittings and relief vent plug. Kleerband® wraps around the flange and is also available in stainless steel with sponge rubber sealing gasket. All sizes available.



## Integra II SSAFS® Gaskets

API 6FB approved fire-safe isolation gasket kits that provide exceptionally dependable isolating and sealing capabilities for severe service applications. Featuring a seal that can withstand temperatures up to 1292 °F and proprietary coated hardened steel washers. Available in classes up to ANSI 2500# and API 10,000#.



## Integra SSA® Gaskets

Constructed from an extremely intense, compressive strength material and formulated for high temperatures. Integra SSA® is recommended for severe service applications and is available in ANSI 150#, up to API 10,000# ratings in a large variety of sizes. Eliminates potential leaks of fugitive emissions.



## Low-Profile, High Strength Casing Spacer Rollers

Patent-pending, cost competitive rollers manufactured exclusively for APS casing spacers. Can carry heavy loads while reducing the coefficient of friction by 70 percent; thus, increasing the average speed of installation from 3 ft. per minute to 15+ ft. per minute.



## Casing Spacers

Field-changeable modular runners are available for casing spacers with 8" wide bands. Casing spacers are available in stainless steel and fusion coated polymer steel bands with 8" and 12" widths, sizes 2" to 120".



## Integra II SSA® Gaskets

Dependable gaskets used for both insulating and general sealing purposes in severe service applications. Suitable in all services up to ANSI 2500# and API 15,000# classes. Exclusively designed for hard environmental applications, especially where hydrocarbons are a factor.



## Safety Spray Shields

PTFE, polypropylene, PVC, polyethylene, 304 & 316 stainless steel metal shields for preventing spray out of hazardous chemicals due to gasket or packing failure on flanges, valves and expansion joints. Sizes range from 1/2" to 72".



## Radolid® Nut & Bolt Protection Caps

Bolt and nut protection caps are used to prevent corrosion on fasteners. Injection molded of low density polyethylene with VCI (Volatile Corrosion Inhibitor) which builds up under the caps to help prevent corrosion. Available in sizes from 1/4" to 3 3/4" bolt diameter.



# Product Summary

Accessories for your pipeline needs.

PO Box 60399  
Lafayette, LA 70596-0399  
Toll Free: (800) 315-6099  
sales@apsonline.com  
www.apsonline.com  
ISO 9001:2015 Registered



## Innerlynx® Modular Mechanical Seals

Molded rubber pipe wall penetration seals can be used in treatment plants, valve vaults, tanks and containment dikes. Available in EPDM, nitrile, silicone, and UL three hour fire-rated styles.

## Foreman Nite Caps

Cast aluminum temporary pipe plugs, sizes 2" to 48". Prevents unwanted foreign materials, small animals, mud or water from contaminating a pipeline.

## Inspect-a-Lift® Pipe Supports

Provides the proven solution to crevice corrosion at pipe supports. Allows for easy inspection to DOT compliance and no metal to metal contact. Eliminates standing water and prevents corrosion.

## Isojoint® Monolithic Isolating Joint

Monolithic isolating joint available in 1/2" to 150" diameter. ANSI 150# to 2,250# and up to API 10,000#. API 5L grade B to X70 materials. Manufactured in all types of carbon and stainless steel.

## Casing End Seals

End seals are available in pull-on, wrap-around Buna-N and zipper styles in eccentric and concentric types for all size carrier/casing pipes, and molded pull-on for concentric installations only.

## Bore Spacers

Designed to support and cradle conduit for ease of installation, allowing optimal free flow of grout and eliminating voids. Maintain accurate duct bank position and alignment that will result in reduced installation time.

## Infinity® Wall Sleeves

Manufactured of HDPE in sizes 2" - 25". Designed for concrete poured barriers to construct a circular penetration through walls, floors, and ceilings. Used with Innerlynx® modular mechanical seals.

## Duocon Centralizers

Manufactured from injection-molded, high density polyethylene. Used to support and space a section of pipe inside a secondary pipe on dual containment systems. Grooves molded into the inner surface prevent slippage and cold flow. Sizes available from 2" to 12" with a standard runner height of 1".

## Raq-gard®

Lightweight, injection-molded, glass-filled polymer isolators that eliminate corrosion between pipes and I-beams.

## Kleergel®

This high-performance grease executes well at high and low temps (-50 °F to 500 °F). Dielectric and hydrophobic, USDA H-1 category approved for incidental food contact.

## Gal-vo-plast® Wall Sleeves

Manufactured of Gal-vo-plast® coated steel, stainless steel, painted steel and plastic in sizes 2" - 100".

