

# RE-SERIES REFERENCE ELECTRODES

## MODEL RE-5:

Flat surface ceramic plug for general use on soil surfaces. Approx. overall size 1 3/8" dia. X 6" long. Dry weight: 4 oz.



Item #15108

## COPPER/COPPER SULFATE ELECTRODES

### MODEL RE-5C:

Ceramic plug has conical shape designed for use in soft soil conditions. Approx. overall size 1 3/8" dia. X 6 3/4" long. Dry weight: 5 oz.



Item #15210

### MODEL RE-7:

Ceramic plug has a flat surface with beveled edge for general purpose use on soil surfaces. Fits through 1 inch diameter holes in pavement & asphalt, for example. Approx. overall size: 1" dia. X 8 1/2" long. Dry weight: 5 oz.



Item #15301

### MODEL RE-375:

Small diameter electrode (non-extendable) designed for readings taken through small holes or cracks. Comes in de-ionized water (DW) and antifreeze (AF) versions. Length: 6 1/2" Diameter: 3/8 inch



RE-375 (DW): Item #15102  
RE-375 (AF): Item #15104

### MODEL RE-2.5U:

Highly durable, large area ceramic plug (2.25" diameter). Electrode can be used in any orientation, including upside down configuration. Ideal for concrete corrosion potential mapping (bridge decks, parking garages, etc.) - stands upright by itself. Electrode supplied with highly absorbent sponge cap for enhanced electrical contact to concrete surfaces.



Item #14905

### FREE-STANDING RE-5C ELECTRODE:

Allows readings to be taken without the technician having to hold onto a reference electrode. Includes a RE-5C electrode (Item #15210). Highly durable plastic stake with stainless steel clip. Length: 15" Width: 1 3/4" Depth: 3 1/2"



Item #15310



# ACCESSORIES

## SUBMERSIBLE ADAPTERS:

Coverts any MCM electrode for use underwater, includes your choice of a lead length (8', 25', 50', 100', 150' or 200') with banana plug. Water-tight connection.



Item #16305  
(8 foot model shown)

## EXTENSIONS:

Intermediate electrode extension: 30" long. One or more can be used with MCM model IA and LC series meters or between the electrode and the standard electrode extension, so that the electrode can be easily placed at the desired location inside manholes, water tanks, etc. Will fit through 1" diameter augered hole.



Item #16203

## ELECTRODE EXTENSIONS:

Electrode extensions 30" long. Side terminal connection allows use of the electrode without bending over or stooping. Extensions also available in 15" lengths.



Item #16101

## ANTI-FREEZE SOLUTION:

For use with any MCM electrode. Permits potential measurements with temperature as low as -10°F (-23°C) without danger of cracking electrode tube. Available in 8 oz. and 32 oz. (fl.) containers. Can be used year around.



Item #17207



Item #17105

## COPPER SULPHATE:

Finely divided high-purity crystals. Available in ¾ lb and 2 ½ lbs containers. Under normal conditions a ¾ lb container will be sufficient to maintain an electrode for a year.



Item #17003



Item #16906

## LEAK STOP GEL:

New, improved Leak Stop Gel for use with any MCM electrode. Stops the leaking of  $\text{CuSO}_4$  electrodes, has no expiration date

Item #18020

Item #18010

